

CHINA LUZHONG TRACTOR - 中国鲁中拖拉机

Luzhong Farm Tractor / 40-55hp 2WD Tractor

| Model | | LZ400 | LZ450 | LZ500 | LZ520 | LZ550 | |
|---------------------------|-----------------------------|-----------------------------------------------|----------------------------------|---------|---------|-------|--|
| Type | | 2WD Wheeled Type | | | | | |
| (mm)Dimensions of Tractor | Length(With front ballast) | 3835 | | | 3880 | 3855 | |
| | Width | 1620 | | | 1750 | 1750 | |
| | Height(to the exhaust vent) | 2135 | | 2210 | | 2130 | |
| | Tread | Front Wheel | 1300 or 1200~1500 Adjusted | | | | |
| | | Rear Wheel | 1300 Fixed or 1200~1500 Adjusted | | | | |
| | Axle Base | 1910 | | 1994 | | 2081 | |
| | Min.Ground Clearance | 410 | | | 400 | | |
| (kg) Structure weight | | 1665 | | 1734 | | 1790 | |
| Ballast weight (kg) | Front ballast | 112 | | 140 | | | |
| | Rear ballast | 100 | | 200 | | | |
| Rated traction force (kg) | | 830 | 850 | 880 | 890 | 950 | |
| Engine | Model | L3105ABT-1(EP/ | JD495T | JD4100T | JD4102T | 4105 | |
| | Type | Vertical,4-Cylinder,Water Cooled and 4-stroke | | | | | |
| | Rated Power(kw) | 29.4 | 33.1 | 36.75 | 38.2 | 40.4 | |
| | Rated speed (r/min) | 2400 | | | | | |
| | Fuel | Diesel | | | | | |
| Tyre | Front Wheel | 6.00-16 | | | | | |
| | Rear Wheel | 12.4-28 | | | | | |
| Clutch | | Dual-stage clutch | | | | | |
| Steering | | power steering | | | | | |
| Transmission Type | | 8+2 or (8+8 with shuttle gearshift) | | | | | |
| Suspension Type | | 3-point links | | | | | |
| PTO | Type and Rev | Semi-independent Type 540/1000 | | | | | |
| | Spline Size | F35 Rectangle Spline with 6 teeth | | | | | |

E-mail: sale@luzhongtractor.com Web: www.luzhongtractor.com

CHINA LUZHONG TRACTOR - 中国鲁中拖拉机



E-mail: sale@luzhongtractor.com

Web: www.luzhongtractor.com